

CONNECTION SWIRL WITH SWIVEL

Stainless steel

Item no. **10176**



SPECIFICATION

RRP / excl. VAT

ITEM NO.	10176
WEIGHT KG	0,350 kg
DIMENSIONS	L 144 mm Ø 30 mm
FORK Ø	12 mm
TENSILE LOAD	1500 kg
MATERIAL	Stainless steel

ADVANTAGES

- **Stainless steel**
Corrosion-free
- **Highest quality ballbearings**
- **Top price to performance ratio**

DESCRIPTION

The connection swirl is used to connect the RUNPOTEC polyester towing rope with the pulling cable or with the pulling grip and to provide twist compensation. Optionally suitable in combination with the RUNPOTEC CW 800 E capstan winch.

Made of stainless steel with highest-quality ballbearings – this makes the RUNPOTEC connection swirl completely corrosion free and therefore one of the highest-quality products on the market.



SAFETY NOTICE:

Not suitable for the vertical cable pull, may not be used to bear/lift loads or people.

INFORMATION

Available as accessories:

POLYESTER PULLING ROPE incl. steel cage

Rope Ø: 8 mm, 10 mm and 12 mm
Lengths of 120 m to 350 m

POLYESTER PULLING ROPE on drum

Rope Ø: 8 mm, 10 mm and 12 mm
Lengths of 120 m to 350 m

Matching pull system:

Capstan winch CW 800 E + Trolley
Art. no. 10138

